

STANDARD INCLUSIONS

Anything but standard.

HEAD OFFICE 29 KEILOR PARK DRIVE, KEILOR PARK VIC 3042

T: (03) 8331 3500

E: INFO@NOSTRAHOMES.COM.AU
W: NOSTRAHOMES.COM.AU

Nostra Homes and Developments Pty Ltd standard specifications are subject to change without notice and we reserve the right to substitute any items with equivalent products at anytime. Please note that various items that may be displayed in our homes may not be included in our standard specifications. Carpets, tiles and bricks provided as standard are from the category 1 builders range only.





HOMES BY NOSTRA

NOTE: Contract Documentation, Bonus Packages and/or Variations may alter or overrule any items listed herein.

CLIENT SIGNATURE

DATE

GUARANTEE

- ► 25 year structural guarantee
- ► Public liability insurance
- ► Construction insurance
- ► Warranty insurance
- ► Builders insurance

AUSTRALIAN MADE KITCHEN

- ► 20mm stone to all benchtops within kitchen
- ► 20mm stone waterfall to one side of kitchen island bench with backdrop
- Designer colour range laminated overhead cabinetry including 20mm overhang & painted plaster feature bulkhead above
- ▶ Designer colour range laminated base cabinetry including recessed-rails Note: 16mm shadow line to base cupboards and drawers if standard handles are chosen. Shadowline is not applicable to recessed-rails.
- ► Laminate overhead cupboard to fridge space with open shelf
- ► Two pot drawers either side of oven (four in total, refer to plans)
- Double end bowl stainless steel sink with chrome mixer
- ► Tiled ceramic splashback to kitchen with your choice of colour
- ► Cold water point to fridge cavity

SMEG APPLIANCES

- ► World class and European made
- ► 900mm, Smeg classic thermoseal, built in electric underbench oven (SFA9310XR)
- ▶ 900mm, Smeg 5 burner gas cooktop (CIR93AXS3)
- ► 900mm high powered Smeg concealed undermount rangehood (PUM901X)
- ► 600mm, Smeg underbench freestanding dishwasher (DWAU6214X)
- ► Externally vented rangehood flute

BATHROOM AND ENSUITE

- ▶ 20mm stone to benchtop vanity
- ► A choice of 6 Vitreous china designer basins with chrome flick mixers
- ► Full laminate cabinets including recessed-rails
- Note: 16mm shadow line to base cupboards and drawers if standard handles are chosen. Shadowline is not applicable to recessed-rails.

- Recessed laminate kicker to vanity
- Semi framed pivot door screen to all showers
- ► Wall mounted shower set on rail with chrome mixer
- Tiled shower bases to all showers
- ► Minimum 1200mm ensuite shower (refer to plans)
- 2 metre high ceramic wall tiles to shower walls with your choice of colour
- ► Polished edge mirrors 950mm high by the width of the vanity
- ► Ceramic wall tiles 200mm above vanities
- ▶ 1665mm white acrylic bath tub with chrome flick mixer and spout
- Ceramic wall tiles 400mm above bathtub
 Ceramic tiles from Bath edge to floor
- Chrome towel rail holder to bathroom and ensuite

CARPETS AND TILES/LAMINATE TO ENTIRE HOME

- ► Your choice of laminate flooring or 450mm x 450mm Ceramic floor tiles to main living area, kitchen, meals and main hallway (excluding study, family, theatre) to ground floor only
- ► Your choice of 450mm x 450mm Ceramic floor tiles to bathroom, ensuite, toilet and laundry (as per plans)
- Carpet to all bedrooms and remainder of the home (refer to standard plans for layout)

CEILINGS

- ▶ 2590mm high ground floor ceilings on all designs
- ► 2440mm high ceilings to first level of double storeys
- ▶ 90mm cove cornices throughout entire home

BRICKWORK AND EXTERNAL CLADDING

SINGLE STOREY HOMES

- ► Selection of bricks from builders range
- Brick infills above all windows, passage doors and garage door

DOUBLE STOREY HOMES

► Selection of bricks from builders

- range to ground floor
- Choice of colour render finish to polystyrene panels to first floor
- Brick infills above windows and external doors to entire ground floor
- ► Brick infills above garage

FOUNDATION

- ► Allowance for up to 300mm cut and fill for level building platform
- ► Engineered H1 Class 25mpa concrete slab, 400mm thick with SL82 steel reinforcement as a minimum

FRAMING

- ► Provide recommended lintels and beams as per engineering
- ► Stabilised machine graded pine (MGP10) wall frames
- ► 450mm stud wall spacing throughout entire frame, including load and nonload bearing walls
- Engineered designed roof trusses at a 22.5 degree pitch (Certain double storey designs are flat deck specific)

FACADE

- ► Architecturally designed facades
- ► Facade includes either full or part render as noted in approved architectural drawings

GARAGE

- ► Electric Panel lift Colorbond garage door with 3 remote controls - 2 hand held and 1 wall mounted
- Brickwork above front garage door supported by steel lintel beam
- ► Double powerpoint to garage
- ▶ Double LED tube lighting to garage
- ► 2040mm x 820mm Internal Access door with Gainsborough brushed chrome passage handle
- ► 2040mm x 820mm External Access door with keyed lock entrance set to gain access to the rear yard

ELECTRICAL

- Automated Go Smart technology to all standard LED Downlights to living, hallway and kitchen living areas (as per plan)
- ► Batten holder lights to remainder of home
- ► Two Double Powerpoints to master bedroom

- ► One Double powerpoint to each room
- ▶ One Telephone point
- Two T.V Points
- ► One Rear flood light
- ► Batten holder light to front porch
- ▶ Direct hard wired smoke detectors
- ► Exhaust fan to main bathroom
- ► Exhaust fan to ensuite
- Safety switches residual current devices

LAUNDRY

- ► Full laminate cabinet with recessedrails base cabinetry and benchtop
- ► Stainless steel 45lt insert trough and chrome mixer

TOILETS

- ► Vitreous china close couple suite, with soft close seat
- ► Toilet roll holders

SECURITY

- ► Keyed locks to all windows
- Gainsborough trilock entrance set to front entry door providing increased security

DOORS AND FINISHES

- ► Front Entry Door: A choice from a selection of 2040mm high x 820mm wide glass insert solid core doors with Gainsborough trilock entrance set
- ► Internal Doors: 2040mm high flush panel doors with Gainsborough brushed chrome passage handles
- Air cushioned door stops to all internal doors
- ► External Laundry Door: 2110mm high x 1450mm wide glass sliding door with aluminium frame (floor plan specific)
- Chrome cylinder knob to robe and linen cupboards

SKIRTING AND ARCHITRAVES

- ► 100mm high tiled skirting to laundry, bathroom, ensuite and toilet
- 67mm x 18mm Primed MDF skirting boards to remainder of home
 67mm x 18mm Primed MDF architraves around doors and

windows

STAIRS - FLOOR PLAN SPECIFIC

► Carpet lined, refer to working drawings for staircase detail

SHELVING

- ► One 450mm deep shelf to all walk in and built in robes
- Chrome hanging rails to all walk in and built in robes
- Four 450mm deep shelves to walk in pantry or pantry
- ► Three 450mm deep shelves to all linen cupboards

HEATING

► Bonaire gas ducted heating with thermostat, number of points and unit size are floor plan specific

HOT WATER SYSTEM

► Rinnai gas boosted solar hot water unit, 5 star rated with never ending flow of hot water

PAINT

- ► Dulux 3 coat paint system 2 full coats initially with 3rd full coat to walls painted prior to handover
- ► Dulux Washable Low Sheen Acrylic Paint to all internal walls
- ► Flat Acrylic Paint to all ceilings
- Dulux High Gloss Enamel Paint to all interior woodwork
- ► Dulux High Gloss Enamel Paint to all internal doors
- ► Exterior Grade Paint to all exterior woodwork

WINDOWS

- Aluminium awning windows to front facade
- ► Sliding windows with clear glazing to remainder of home
- ► Keyed locks to all windows
- Double Storey floor plans only: Double glazing to all windows only (does not include sliding doors or double glazing for additional windows added to home)

ALFRESCO - FLOOR PLAN SPECIFIC

► Flat Acrylic paint to complete plasterlined ceiling

► Concrete floor which is poured at slab stage

BALCONIES - FLOOR PLAN SPECIFIC

► Refer to working drawings for balcony detail

ROOF TILES

- Selection of concrete roof tiles from builders range
- Zinc flat deck metal roofing to certain double storey designs

ROOF PLUMBING

- ► Colorbond fascia
- Colorbond gutters
- Colorbond downpipesColorbond cappings
- Maintenance free and corrosion performance
 Note: Zinc flat deck roofing comes with zinc box gutters

INSULATION

- INSOLATION
- ► Sisalation wall wrap
- R1.5 wall batts to external walls
 R2.5 insulation wool to ceiling cavity to all habitable rooms

PRELIMINARIES

- ► Soil test by a geotechnical engineer
- Site survey by a certified land surveyor
- Required council documents and building permits
 Personalised one on one colour
- selection at Nostra Select Showroom
 ► Asset protection

CONNECTIONS

- ► Connections to stormwater, sewer, mains gas, mains water and underground power connections based on a maximum 5m home set back on an allotment up to 612m2 (excludes consumer connection fees and utility account opening fees)
- 2 Garden taps provided 1 inside the front boundary and 1 attached to the rear of the home

Version 1.13